




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 5/00	A2	(11) International Publication Number: WO 99/65230 (43) International Publication Date: 16 December 1999 (16.12.99)
(21) International Application Number: PCT/IB99/01012 (22) International Filing Date: 3 June 1999 (03.06.99) (30) Priority Data: 98201975.4 12 June 1998 (12.06.98) EP (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventors: SOEPENBERG, Gerrit, H.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). TOL, Ronald, M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: GROENENDAAL, Antonius, W., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).		(81) Designated States: CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: TRANSMISSION SYSTEM**(57) Abstract**

The transmission system comprises a transmitter (10) and a receiver (14). The transmitter (10) can transmit a multiplex signal (12) to the receiver (14). The multiplex signal (12) comprises a periodically repeated plurality of modules (42), whereby the modules (42) each comprise at least one object (32, 36, 40). The receiver (14) comprises extracting means (16) for extracting objects (32, 36, 40) from the multiplex signal (12). The extracting means (16) are embodied so as to extract the objects (32, 36, 40) in dependence on module related information present in the multiplex signal (12).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Transmission system.

The invention relates to a transmission system for transmitting a multiplex signal from a transmitter to a receiver, said multiplex signal comprising a periodically repeated plurality of modules, the modules each comprising at least one object, the receiver comprising extracting means for extracting objects from the multiplex signal.

5 The invention further relates to a transmitter for transmitting a multiplex signal, a receiver for receiving a multiplex signal and a multiplex signal comprising a periodically repeated plurality of modules.

10 A transmission system according to the preamble is known from ISO/IEC International Standard 13818-6, "MPEG-2 Digital Storage Media Command and Control" July 12, 1996. In modern digital broadcast systems a transmitter, e.g. a headend, typically transmits a large number of services (or channels) to a plurality of receivers, like for instance television sets or set-top boxes. Such a service can contain an audio/video stream, an interactive
15 application (for example in the MHEG-5 format), other kinds of data or a combination of these elements. An MPEG-2 transport stream is a multiplex of a number of services. Typically, a transmitter transmits several transport streams to the set-top boxes. A set-top box can tune to a specific transport stream and is then able to retrieve information from the transport stream. Such a set-top box typically has only one tuner and is thus merely able to receive one single
20 transport stream at a time. When a user wants to look at a television program, or wants to run an interactive application, or wants to access other kinds of data the set-top box or television set tunes to the corresponding transport stream and retrieves and processes the required data from the service as it is being broadcast at that moment.

25 Interactive applications like for instance tele-banking, tele-shopping or an electronic newspaper are typically broadcast in a carousel-like fashion, i.e. the therewith corresponding data sections are repeated periodically in the transport stream. For instance, both DVB and DAVIC have specified DSM-CC object carousels as known from the above mentioned document for broadcasting interactive applications. The response time of this kind of applications can be improved considerably by applying some kind of caching in the set-top

box, i.e. pre-fetching and storing data sections in the set-top box which are likely to be accessed in the future. Otherwise, if pre-fetching and caching is not used and the set-top box wants to retrieve a part of the interactive application, the set-top box must wait until that particular part is broadcast again. In order to be able to cache data, the set-top box must have access to a storage device like for instance a hard disk. The set-top box can also use this storage device to store linear television content, like for instance short news bulletins or weather forecasts. These programs can be viewed by the user whenever this is convenient.

The objects of a DSM-CC object carousel are broadcast in modules. Such a module is a container of objects and comprises a number of DownloadDataBlock messages (which are MPEG-2 private sections). When a set-top box wants to pre-fetch a DSM-CC object, it must (among other things) know in which module the object resides. After it has retrieved the right module, the set-top box must parse the module to get to the object itself. Due to the hierarchical nature of the DSM-CC object carousel an object might be included in a subdirectory. If this is the case, the set-top box must also retrieve the module(s) with the intermediate directories, and parse them before it gets to the object in which it is interested. Typically, the service provider broadcasts the object carousel in a compressed form. This compression is normally done at the module level. Thus, retrieving an object requires also the decompression of all the modules that are needed for the retrieval of the objects the set-top box is interested in. So, making use of the hierarchical nature of the DSM-CC object carousel for the purpose of pre-fetching objects requires a lot of processing in the set-top box.

An object of the invention is to provide a transmission system, wherein the receiver is able to pre-fetch objects in a relatively simple manner. This object is achieved in the transmission system according to the invention, which is characterized in that the extracting means are embodied so as to extract the objects in dependence on module related information present in the multiplex signal. By including module related pre-fetch information in the transport stream, for instance by adding a pre-fetch tag to all modules, the receiver does not need to parse any module during the pre-fetching process. Furthermore, the receiver can store the modules efficiently, i.e. modules which are transmitted in a compressed form can be stored in that compressed form. A third advantage of this set-up is that it is easy to find out which modules should be pre-fetched.

An embodiment of the transmission system according to the invention is characterized in that the module related information is contained in a single information section. By concentrating the module related pre-fetch information for all modules included in the transport stream into a single information section the receiver can quickly get a complete
5 view of all pre-fetchable modules included in the transport stream by simply reading this information section. In this way, the receiver can easily find out which modules it has to pre-fetch.

10 The above object and features of the present invention will be more apparent from the following description of the preferred embodiments with reference to the drawings, wherein:

Figure 1 shows a block diagram of a transmission system according to the
15 invention,

Figure 2 shows a diagram of the layering used in DSM-CC object carousels.

20 Figure 1 shows a block diagram of a transmission system according to the invention. In such a transmission system a number of multiplex signals 12 are transmitted by a transmitter 10 to a receiver 14. The transmission system may comprise further receivers 14. The transmission system according to the invention can be used in a cable television (CATV) network environment, whereby the transmitter 10 comprises the headend of the CATV-
25 network and the receivers 14 comprise the set-top boxes or the television sets of the end-users. The end-users are able to control a receiver 14 by means of an input device 15, like for instance a keyboard or a remote control. The end-users can view the selected services on a display device 17.

The multiplex signals 12 can be implemented in the form of MPEG-2 transport
30 streams. An MPEG-2 transport stream is a multiplex of a number of so-called services. Such a service can contain an audio/video stream, an interactive application (for example in the MHEG-5 format), other kinds of data or a combination of these elements. Typically, a headend 10 transmits several transport streams 12 to the set-top boxes 14. In this way, a large

number of services (or channels) can be broadcast by the headend 10 to a plurality of set-top boxes 14.

A set-top box can 14 tune to a specific transport stream 12 and is then able to retrieve information from the transport stream 12. Such a set-top box 14 typically has only one
5 tuner and is thus merely able to receive a single transport stream 12 at a time. When a user wants to look at a television program, or wants to run an interactive application, or wants to access other kinds of data the set-top box 14 tunes to the corresponding transport stream 12 and retrieves and/or processes the required data from the service as it is being broadcast at that moment.

10 Interactive applications like for instance tele-banking, tele-shopping or information services are typically broadcast in a carousel-like fashion, i.e. the therewith corresponding data sections are repeated periodically in the transport stream 12. For instance, both DVB and DAVIC have specified DSM-CC object carousels for broadcasting interactive applications. The response time of this kind of applications can be improved considerably by
15 applying some kind of caching in the set-top box 14, i.e. pre-fetching and storing data sections or objects in the set-top box which are likely to be accessed in the future. This pre-fetching of objects from the transport stream 12 is performed by extracting means 16, which extracting means 16 are included in the set-top box 14. Otherwise, if pre-fetching and caching is not used and the set-top box 14 wants to retrieve a part of the interactive application, the set-top box 14
20 must wait until that particular part is broadcast again. In order to be able to cache data, the set-top box 14 must have access to a storage device 19 like for instance a hard disk. The set-top box 14 can also use this storage device to store linear television content, like for instance short news bulletins or weather forecasts. These programs can be viewed by the user whenever this is convenient.

25 One particular example of an interactive application is an electronic newspaper. This application can consist of many objects in the carousel. These objects are to be presented to the user in some manner, e.g., a *viewer* application presents a front page representing the table of contents with links to other elements of the newspaper. Typical elements are: headlines, current affairs in politics, sports, the weather, etc. These elements are typically only
30 relevant for a limited time and they can be replaced by more recent ones.

With respect to an electronic newspaper application the following steps can be distinguished:

Step 1: Subscribing

An end-user can subscribe to an electronic newspaper of some service provider. He can indicate in which parts of the electronic newspaper he is interested (e.g. sports, financials, and headlines).

Step 2: Setting a filter

- 5 Based on the end-users' preferences, the electronic newspaper application will construct a *filter*, which is responsible to cache (pre-fetch) objects related to the service on local storage. For example, a filter can specify that all objects related to sports, financials or headlines should be pre-fetched (by the extracting means 16) and cached on the storage device 19.

Step 3: Filtering and caching the data

- 10 Once one or more filters have been set, the set-top box can start looking for the right data, retrieve it from the broadcast stream and cache it on local storage. This filtering is an ongoing process.

Step 4: Viewing

- 15 Once an end-user has subscribed to the electronic newspaper, he can select that application and view the parts in which he was interested. Naturally, the objects needed to present those parts must have been retrieved first during filtering (step 3).

- 20 The above mentioned filters can be specified using the hierarchical nature of the DSM-CC object carousel. For instance, a filter can specify that all objects in a specific subtree, e.g. /apps/newspaper/sports, have to be pre-fetched. This approach has, however, a number of disadvantages. To explain this some knowledge on DSM-CC object carousels is needed.

- 25 In Figure 2 the layered structure of DSM-CC object carousels is shown. The objects of a DSM-CC object carousel are broadcast in modules. Such a module is a container of objects and comprises a number of DownloadDataBlock messages (which are MPEG-2 private sections). In Figure 2 module 42 comprises the objects 32, 36 and 40. These objects are included in so-called BIOP-messages. In such a BIOP-message the object is preceded by a message header. In Figure 2 a first BIOP-message comprises a message header 30 and the object 32, which object 32 may include directory information. A second BIOP-message
30 comprises a message header 34 and the object 36, which object 36 may include stream information. A third BIOP-message comprises a message header 38 and the object 40, which object 40 may include file information.

Furthermore, the module 42 comprises five DownloadDataBlock messages. These DownloadDataBlock messages consist of a header and a data block. The first

DownloadDataBlock message is formed by header 44 together with data block 46, the second DownloadDataBlock message is formed by header 48 together with data block 50, etc.

When a set-top box wants to pre-fetch a DSM-CC object, it must (among other things) know in which module the object resides. After it has retrieved the right module, the set-top box must parse the module to get to the object itself. Due to the hierarchical nature of the DSM-CC object carousel an object might be included in a subdirectory. If this is the case, the set-top box must also retrieve the module(s) with the intermediate directories, and parse them before it gets to the object in which it is interested.

Typically, the service provider broadcasts the object carousel in a compressed form. This compression is normally done at the module level. Thus, retrieving an object requires also the decompression of all the modules that are needed for the retrieval of the objects the set-top box is interested in.

The disadvantages of using the hierarchical nature of the object carousel for a filter specification are as follows. First, it requires that the set-top box must parse the module that contains an object in which the set-top box is interested. It must also parse the modules that contain an intermediate directory object in the path to the object. Also, all the directory objects in the specified sub-tree must be parsed, so the set-top box knows which other objects are part of the sub-tree. In short, this requires a lot of processing. Second, the set-top box must often decompress modules (in case they are compressed). However, the set-top box ideally wants to store the objects in local storage in a compressed form. This means that first a module is decompressed and that subsequently the individual objects are compressed. This is waste of processing power.

An efficient way for specifying a filter is to say that a filter should filter all modules that have a certain tag attached. This means that the filter no longer works at the object carousel layer, but at the module level (i.e., the data carousel layer). The advantages of this are that the set-top box no longer needs to parse any module when pre-fetching and that it can store modules in a compressed form if they were broadcast in compressed form, thus saving storage space.

Another advantage is that it is easy to find out which modules should be pre-fetched. The service provider periodically broadcasts a message listing the modules that are part of an object carousel, the 'DownloadInfoIndication' message. This message contains for each module a 'ModuleInfo' structure. This structure has a field 'userInfo'. The DSM-CC standard does not specify the use of this field; it is meant as an extension mechanism. This 'userInfo' field can easily contain the module tags. Thus, the set-top box retrieves the

'DownloadInfoIndication' message(s), and compares for each module the listed tags (in the 'userInfo' field) with the tags in the filter. If a tag matches, it pre-fetches the module.

Finally, it is easy to see whether a pre-fetched module needs updating. DSM-CC assigns to each module a version number (listed in the 'DownloadInfoIndication' message). Thus, to check whether a pre-fetched module is still up-to-date, the set-top box retrieves again the 'DownloadInfoIndication' message and compares the version numbers.

Next to the tag attribute, it may be desirable to add other attributes to modules. For instance, an expiration date attribute can tell the set-top box when the set-top box should remove the pre-fetched module (e.g., because it no longer valid or relevant). Another example is a cache priority attribute. The set-top box can use this cache priority to determine which modules it should pre-fetch and which not, when there is not enough storage space to pre-fetch them all.

CLAIMS:

1. A transmission system for transmitting a multiplex signal (12) from a transmitter (10) to a receiver (14), said multiplex signal (12) comprising a periodically repeated plurality of modules (42), the modules (42) each comprising at least one object (32,36,40), the receiver (14) comprising extracting means (16) for extracting objects (32,36,40) from the multiplex signal (12), characterized in that the extracting means (16) are embodied so as to extract the objects (32,36,40) in dependence on module related information present in the multiplex signal (12).
2. A transmission system according to Claim 1, characterized in that the module related information is contained in a single information section.
- 10 3. A transmitter (10) for transmitting a multiplex signal (12), said multiplex signal (12) comprising a periodically repeated plurality of modules (42), the modules (42) each comprising at least one object (32,36,40), characterized in that the transmitter (10) is embodied so as to insert in the multiplex signal (12) module related object extraction information.
- 15 4. A transmitter (10) according to Claim 3, characterized in that the module related object extraction information is contained in a single information section.
5. A receiver (14) for receiving a multiplex signal (12), said multiplex signal (12) comprising a periodically repeated plurality of modules (42), the modules (42) each comprising at least one object (32,36,40), the receiver (14) comprising extracting means (16) for extracting objects (32,36,40) from the multiplex signal (12), characterized in that the extracting means (16) are embodied so as to extract the objects (32,36,40) in dependence on module related information present in the multiplex signal (12).
- 20 6. A receiver (14) according to Claim 5, characterized in that the module related information is contained in a single information section.
- 25 7. A multiplex signal (12) comprising a periodically repeated plurality of modules (42), the modules (42) each comprising at least one object (32,36,40), characterized in that the multiplex signal (12) further comprises module related object extraction information.
8. A multiplex signal (12) according to Claim 7, characterized in that the module related object extraction information is contained in a single information section.

1/1




FIG. 1




FIG. 2

This Page Blank (uspto)

1/1




FIG. 1




FIG. 2

This Page Blank (uspto)

BNSDOCID: <WO__9965230A3 | >

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB 99/01012

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04N 5/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04N, H04H, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5614940 A (DAVID A. COBBLEY ET AL), 25 March 1997 (25.03.97), column 3, line 26 - column 4, line 36; column 6, line 7 - line 67; column 7, line 48 - column 8, line 16, column 8, line 30 - column 9, line 33 --	1-9
X	US 5418782 A (ANTHONY J. WASILEWSKI), 23 May 1995 (23.05.95), column 2, line 25 - column 3, line 52; column 7, line 23 - column 8, line 40; column 9, line 17 - column 10, line 48, abstract --	1-8

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 January 2000

Date of mailing of the international search report

2000-01-21

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Erik Veillas/MN
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/01012

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5594492 A (DANIEL O'CALLAGHAN ET AL), 14 January 1997 (14.01.97), column 3, line 43 - column 5, line 8; column 8, line 54 - line 65; column 7, line 23 - line 34, figures 1,5, abstract --	1-8
A	EP 0844766 A2 (NOKIA TECHNOLOGY GMBH), 27 May 1998 (27.05.98), column 6, line 30 - line 45; column 7, line 2 - line 35, claim 11 --	1-9
P,X	IEEE Transactions on consumer electronics, Volume 44, August 1998, Stuart Pekowsky et al, "THE SET-TOP BOX AS "MULTI-MEDIA TERMINAL"", see chapters 3,4 --	1-8
P,X	WO 9826528 A2 (SCIENTIFIC-ATLANTA, INC.), 18 June 1998 (18.06.98), see whole document -- -----	1-9

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/IB 99/01012

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	5614940	A	25/03/97	US 5818510 A	06/10/98
US	5418782	A	23/05/95	AU 683134 B	30/10/97
				AU 1560995 A	01/08/95
				CA 2180363 A,C	13/07/95
				JP 2940638 B	25/08/99
				JP 9509293 T	16/09/97
				WO 9519076 A	13/07/95
				AU 6359994 A	26/09/94
				CA 2157670 A	15/09/94
				DE 69420260 D	00/00/00
				EP 0688490 A,B	27/12/95
				JP 8507666 T	13/08/96
				US 5359601 A	25/10/94
				WO 9421085 A	15/09/94
				AU 5575894 A	24/05/94
				BR 9307339 A	01/06/99
				CA 2148270 A	11/05/94
				EP 0682830 A	22/11/95
				JP 8503823 T	23/04/96
				US 5400401 A	21/03/95
				WO 9410775 A	11/05/94
US	5594492	A	14/01/97	US 5477263 A	19/12/95
EP	0844766	A2	27/05/98	FI 102651 B	00/00/00
				FI 964640 A	28/07/98
				FI 970186 A	17/07/98
WO	9826528	A2	18/06/98	AU 7851498 A	03/07/98

Page Blank (uspto)

Page Blank